AUSTRALIAN CHEMICAL REAGENTS

SAFETY DATA SHEET

Date Prepared: July 2018
Version No: 5

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: Multi Element Standard
Product Code: 5092
Other Names:
Uses: Analytical Reagent

Supplier: Australian Chemical Reagents
38-50 Bedford Street Gillman SA 5013

Contacts: Telephone: 61 08 84402000
Fax: 61 08 84402001
Emergency Phone: 61 08 84402000 Mon – Fri 8:30am – 5:00pm

2. HAZARDS INFORMATION

GHS Classification

Skin Corrosion/Irritation: Category 2
Serious Eye Damage/Irritation: Category 2A
Corrosive to metals: Category 1

Signal Word(s)

WARNING

Pictogram(s)



Hazard Statement(s)

H290 May be corrosive to metals: Category 1
H315 Causes skin irritation.
H319 Causes serious eye irritation.

Precautionary Statement(s)

Preventative

P234 Keep only in original container
P264 Wash thoroughly after handling.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response

P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P312 Call a POISON CENTER or doctor/physician if you feel unwell.
P363 Wash contaminated clothing before reuse.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 If eye irritation persists: Get medical advice/attention.
P390 Absorb spillage to prevent material-damage.

Storage	P406 Store in corrosive resistant/... container with a resistant inner liner.
Disposal	P501 Dispose of contents/container to an approved waste disposal plant.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients :

Chemical Entity	CAS No	Proportion
Zinc nitrate	[10196-18-6]	1.5%
Copper nitrate	[19004-19-4]	0.8%
Manganese nitrate	[17141-63-8]	2.5%
Lead nitrate	[10099-74-8]	0.3%
Arsenic(V) oxide	[12044-50-7]	<0.1%
Cadmium nitrate	[10022-68-1]	trace
Selenious acid	[7783-00-8]	trace
Nitric acid	[7697-37-2]	2%
Water	[7732-18-5]	to 100%

4. FIRST AID MEASURES

Safety showers and eye wash facilities should be provided.

Swallowed :

If conscious wash out mouth with water. Seek medical advice. Show this SDS to medical practitioner.

Eye :

Immediately hold eyelids open and flood with water for at least 15 minutes. Obtain medical aid. Show this SDS to medical practitioner.

Skin :

Remove contaminated clothing. Immediately wash skin thoroughly with water and mild soap. Seek medical advice if irritation persists. Show this SDS to medical practitioner. Launder clothing before reuse.

Inhaled :

Remove from contaminated air. Maintain breathing with artificial respiration if necessary. Seek medical assistance. Show this SDS to a doctor.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media:

Water spray. Carbon dioxide, dry chemical powder, or appropriate foam.

Hazards From Combustion Products:

Solutions will not burn or support combustion. Decomposition products include oxides of nitrogen.

Precautions For Fire Fighters and Special Protective Equipment:

Fire fighters and others who may be exposed to combustion products during fire should wear full protective clothing including positive pressure self-contained breathing apparatus (SCBA). Wear SCBA with full face-piece, operated in positive pressure mode when fighting fires.

Hazchem Code: 2X

6. ACCIDENTAL RELEASE MEASURES

Emergency procedures:

Prevent from entering waterways. Restrict access to area. Remove chemicals that can react with the spilled material. Spills are slippery

Methods and materials for containment and clean up:

Use inert material such as sand or earth to contain spill or leak. Absorb spills with chemical absorber or vermiculite and dispose of in accordance with local regulations.

7. HANDLING AND STORAGE

Precautions for Safe Handling:

Do not get in eyes, on skin, on clothing. Avoid prolonged or repeated exposure.

Conditions for Safe Storage:

Store sealed in original container in a cool well ventilated situation away from foods and other chemicals. Do not store in direct sunlight. Observe good hygiene and housekeeping practices.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

National Exposure Standards:
Safe Work Australia – Manganese, dust & compd's (as Mn) TWA 1 mg/m^3; - Lead, inorganic dusts or fumes (as Pb) TWA 0.15 mg/m^3 ; Arsenic and soluble compounds (as As) TWA 0.05 mg/m^3 (Cat 1 carcinogen); Cadmium and compounds (as Cd) TWA 0.01 mg/m^3 (Cat 2 carcinogen); Nitric acid TWA 5.2 mg/m^3 STEL 10 mg/m^3

Biological Limit Values: No data available.

Engineering Controls:
Not required with normal use. If mists are likely to be generated maintain atmospheric concentrations well below exposure standards with extraction ventilation.

Personal Protective Equipment (PPE):
The use of nitrile or neoprene gloves complying with AS 2161 and the use of faceshield, chemical goggles or safety glasses with side shield protection complying with AS/NZS 1337 is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance :	Clear liquid
Odour:	Nil
pH:	1
Boiling Point (^{0}C) :	Not applicable
Freezing/melting Point:	Not applicable
Vapour Pressure (mm of Hg @ 25^{0}C) :	Not applicable
Vapour Density:	Not applicable
Specific Gravity :	1.1
Flash Point (^{0}C) :	Not flammable
Flammability Limits (%) :	Not flammable
Solubility in Water (g/L) :	Soluble

10. STABILITY AND REACTIVITY

Chemical stability:
Stable.
Conditions to avoid:
Acidic solution. Will corrode metals. Will produce toxic gases on contact with cyanides, sulphides etc.
Incompatible materials:
Strong alkalies, powdered metals
Hazardous decomposition products:
Refer to section 5 (Fire Fighting Measures).
Hazardous reactions:
Hazardous polymerization will not occur.

11. TOXICOLOGICAL INFORMATION

Health Effects:
Swallowed : Harmful if swallowed. May burn or irritate gastric tissue. For cadmium LD50 oral rat 225mg/kg. For arsenic oral-man LD50 1430 ug/kg , LD50 oral rat 40mg/kg.

Eye : Irritating to eye tissue.

Skin : Harmful if absorbed through skin. May irritate skin tissue with prolonged contact.

Inhaled : Harmful if inhaled. Inhalation of vapours may irritate nose and throat. Inhalation of mists into lungs can cause pneumonitis. For cadmium inhalation human LCLo 39mg/m^3/20 minutes.

Chronic Effects: Cadmium and arsenic are carcinogens. Repeated or prolonged skin contact may cause dermatitis.

12. ECOLOGICAL INFORMATION

Ecotoxicity:
No data available.
Persistence and degradability:
No data available.
Mobility:
No data available.

13. DISPOSAL CONSIDERATIONS

Contact a licensed professional waste disposal service to dispose of this material. Observe all federal, state and local environmental regulations.

14. TRANSPORT INFORMATION

UN Number: 3264
UN Proper Shipping Name: CORROSIVE LIQUID ACIDIC N.O.S (Contains nitric acid 2%)
Class and subsidiary risk(s): 8
Packing Group: III
Hazchem Code: 2X
Special precautions for user : Nil

15. REGULATORY INFORMATION

Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP):
Schedule 5

16. OTHER INFORMATION

Disclaimer:
All information given by the Company is offered in good faith and is believed to the best of our knowledge to be accurate. However this information is offered without warranty representation inducement or licence and the Company does not assume legal responsibility for reliance upon the same.
Every person dealing with the materials referred to herein does so at his or her own risk absolutely and must make independent determinations of suitability and completeness of information from all sources to ensure their proper use.

END of SDS