

SAFETY DATA SHEET

Version 6.10
Revision Date 01.03.2024
Print Date 24.04.2026

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : Toluene

Product Number : 34866
Brand : SIGALD
CAS-No. : 108-88-3

1.2 Other means of identification

No data available

1.3 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : For R&D use only. Not for pharmaceutical, household or other uses.

1.4 Details of the supplier of the safety data sheet

Company : Merck Life Science Pty Ltd
Ground Floor, Building 1, 885 Mountain Highway
BAYSWATER VIC 3153
AUSTRALIA

Telephone : +61 1800 800 097
E-mail address : customersupport.anz@merckgroup.com

1.5 Emergency telephone

Emergency Phone # : Free call (24/7): 1800 862 115
Int'l (24/7): +61 2 9037 2994
(CHEMTREC)

SECTION 2: Hazards identification

2.1 GHS Classification

Flammable liquids (Category 2), H225
Skin corrosion/irritation (Category 2), H315
Reproductive toxicity (Category 2), H361
Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336
Specific target organ toxicity - repeated exposure, Inhalation (Category 2), Central nervous system, H373
Aspiration hazard (Category 1), H304

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal Word

Danger

Hazard Statements

H225 Highly flammable liquid and vapor.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H361 Suspected of damaging fertility or the unborn child.
H373 May cause damage to organs (Central nervous system) through prolonged or repeated exposure if inhaled.

Precautionary Statements

Prevention

P201 Obtain special instructions before use.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P260 Do not breathe mist or vapors.
P264 Wash skin thoroughly after handling.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P331 Do NOT induce vomiting.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

2.3 Other hazards - none

SECTION 3: Composition/information on ingredients

Substance / Mixture : Substance

3.1 Substances

Formula : C₇H₈
Molecular weight : 92.14 g/mol
CAS-No. : 108-88-3
EC-No. : 203-625-9
Index-No. : 601-021-00-3

Hazardous ingredients

| Component | Classification | Concentration |
|----------------|---|---------------|
| Toluene | Flam. Liq. 2; Skin Corr./Irrit. 2; Repr. 2; | <= 100 % |

| | | |
|--|--|--|
| | STOT SE 3; STOT RE 2; Asp. Tox. 1; H225, H315, H361, H336, H373, H304 Concentration limits: 20 %: STOT SE 3, H336; | |
|--|--|--|

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Call in physician.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Consult a physician.

In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

If swallowed

After swallowing: caution if victim vomits. Risk of aspiration! Keep airways free. Pulmonary failure possible after aspiration of vomit. Call a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Foam Carbon dioxide (CO₂) Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Combustible.

Pay attention to flashback.

Vapors are heavier than air and may spread along floors.

Development of hazardous combustion gases or vapours possible in the event of fire.

Forms explosive mixtures with air at ambient temperatures.

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

5.4 Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

Storage class

Storage class (TRGS 510): 3: Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.3 no other specific uses are stipulated.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

| Component | CAS-No. | Value | Control parameters | Basis |
|-----------|----------|-----------------|-------------------------------|--|
| Toluene | 108-88-3 | TWA | 50 ppm 191 mg/m ³ | Australia. Workplace Exposure Standards for Airborne Contaminants. |
| | Remarks | Skin absorption | | |
| | | STEL | 150 ppm 574 mg/m ³ | Australia. Workplace Exposure Standards for Airborne Contaminants. |
| | | Skin absorption | | |

Derived No Effect Level (DNEL)

| Application Area | Routes of exposure | Health effect | Value |
|------------------|--------------------|----------------------------|------------------------|
| Workers | Inhalation | Acute systemic effects | 384 mg/m ³ |
| Workers | Inhalation | Acute local effects | 384 mg/m ³ |
| Workers | Skin contact | Long-term systemic effects | 384mg/kg BW/d |
| Workers | Inhalation | Long-term systemic effects | 192 mg/m ³ |
| Workers | Inhalation | Long-term local effects | 192 mg/m ³ |
| Consumers | Inhalation | Acute systemic effects | 226 mg/m ³ |
| Consumers | Inhalation | Acute local effects | 226 mg/m ³ |
| Consumers | Skin contact | Long-term systemic effects | 226mg/kg BW/d |
| Consumers | Inhalation | Long-term systemic effects | 56.5 mg/m ³ |
| Consumers | Ingestion | Long-term systemic effects | 8.13mg/kg BW/d |

Predicted No Effect Concentration (PNEC)

| Compartment | Value |
|------------------------------|-------------|
| Soil | 2.89 mg/kg |
| Sea water | 0.68 mg/l |
| Fresh water | 0.68 mg/l |
| Sea sediment | 16.39 mg/kg |
| Fresh water sediment | 16.39 mg/kg |
| Sewage treatment plant | 13.61 mg/l |
| Aquatic intermittent release | 0.68 mg/l |

8.2 Exposure controls

Appropriate engineering controls

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact

Material: Viton®

Minimum layer thickness: 0.7 mm

Break through time: 480 min

Material tested: Vitoject® (KCL 890 / Aldrich Z677698, Size M)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Splash contact

Material: Viton®

Minimum layer thickness: 0.7 mm

Break through time: 480 min

Material tested: Vitoject® (KCL 890 / Aldrich Z677698, Size M)

Body Protection

Flame retardant antistatic protective clothing.

Respiratory protection

required when vapours/aerosols are generated. Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- | | |
|--|---------------------------------|
| a) Physical state | liquid |
| b) Color | No data available |
| c) Odor | benzene-like |
| d) Melting point/freezing point | Melting point/range: -93 °C |
| e) Initial boiling point and boiling range | 110 - 111 °C |
| f) Flammability (solid, gas) | No data available |
| g) Upper/lower | Upper explosion limit: 7.1 %(V) |

| | |
|---|--|
| flammability or explosive limits | Lower explosion limit: 1.2 %(V) |
| h) Flash point | 4.4 °C - closed cup |
| i) Autoignition temperature | No data available |
| j) Decomposition temperature | No data available |
| k) pH | Not applicable |
| l) Viscosity | Viscosity, kinematic: No data available Viscosity, dynamic: 0.56 mPa.s at 25 °C |
| m) Water solubility | 0.58 g/l at 25 °C - partly soluble |
| n) Partition coefficient: n-octanol/water | log Pow: 2.73 at 20 °C - Bioaccumulation is not expected. |
| o) Vapor pressure | 30.88 hPa at 21.1 °C |
| p) Density | 0.865 g/mL at 25 °C |
| Relative density | No data available |
| q) Relative vapor density | No data available |
| r) Particle characteristics | No data available |
| s) Explosive properties | No data available |
| t) Oxidizing properties | none |

9.2 Other safety information

| | |
|------------------------|---------------------------------|
| Conductivity | < 0.01 µS/cm |
| Surface tension | 27.73 mN/m at 0.516g/l at 25 °C |
| Relative vapor density | 3.18 |

SECTION 10: Stability and reactivity

10.1 Reactivity

Vapors may form explosive mixture with air.
Vapors may form explosive mixture with air.

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .
The product is chemically stable under standard ambient conditions (room temperature) .

10.3 Possibility of hazardous reactions

Risk of explosion with:
fuming sulfuric acid

Nitric acid
silver
perchlorates
nitrogen dioxide
nonmetallic halides
halogen-halogen compounds
uranium hexafluoride
organic nitro compounds
Violent reactions possible with:
Strong acids
Strong oxidizing agents
sulfur
with
Heat.

10.4 Conditions to avoid

Warming.
Warming.

10.5 Incompatible materials

No data available

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - male - 5,580 mg/kg
(Directive 67/548/EEC, Annex V, B.1.)
LC50 Inhalation - Rat - male - 4 h - 25.7 mg/l - vapor

(OECD Test Guideline 403)

LD50 Dermal - Rabbit - male - > 5,000 mg/kg
Remarks: (ECHA)

Skin corrosion/irritation

Skin - Rabbit
Result: irritating - 4 h
(Regulation (EC) No. 440/2008, Annex, B.4)

Serious eye damage/eye irritation

Eyes - Rabbit
Result: No eye irritation
(OECD Test Guideline 405)

Respiratory or skin sensitization

Maximization Test - Guinea pig
Result: negative
(Regulation (EC) No. 440/2008, Annex, B.6)

Germ cell mutagenicity

SIGALD- 34866

Page 8 of 12

The life science business of Merck operates as MilliporeSigma in the US and Canada



Test Type: In vitro mammalian cell gene mutation test
Test system: Mouse lymphoma test
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: negative
Test Type: Ames test
Test system: *S. typhimurium*
Metabolic activation: with and without metabolic activation
Method: Regulation (EC) No. 440/2008, Annex, B.13/14 (Ames test)
Result: negative

Test Type: Chromosome aberration test
Species: Rat
Cell type: Bone marrow
Application Route: Intraperitoneal

Result: negative
Remarks: (ECHA)

Carcinogenicity

No data available

Reproductive toxicity

Suspected of damaging the unborn child.

Specific target organ toxicity - single exposure

Inhalation - May cause drowsiness or dizziness. - Central nervous system

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Specific target organ toxicity - repeated exposure

Inhalation - May cause damage to organs through prolonged or repeated exposure.

- Central nervous system

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Aspiration hazard

Aspiration may cause pulmonary edema and pneumonitis.

11.2 Additional Information

Repeated dose toxicity - Rat - male and female - Oral - 13 Weeks - NOAEL (No observed adverse effect level) - 625 mg/kg - LOAEL (Lowest observed adverse effect level) - 1,250 mg/kg

RTECS: XS5250000

Drowsiness, irritant effects, Dizziness, Convulsions, Headache, Nausea, Vomiting, Circulatory collapse, somnolence, inebriation, Unconsciousness, respiratory arrest, CNS disorders, respiratory paralysis, death

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

SECTION 12: Ecological information

12.1 Toxicity

SIGALD- 34866

Page 9 of 12

The life science business of Merck operates as MilliporeSigma in the US and Canada



| | |
|---|---|
| Toxicity to fish | flow-through test LC50 - Oncorhynchus kisutch (coho salmon) - 5.5 mg/l - 96 h Remarks: (ECHA) |
| Toxicity to daphnia and other aquatic invertebrates | EC50 - Ceriodaphnia dubia (water flea) - 3.78 mg/l - 48 h (US-EPA) |
| Toxicity to bacteria | static test EC50 - Bacteria - 84 mg/l - 24 h Remarks: (ECHA) |
| Toxicity to fish(Chronic toxicity) | flow-through test NOEC - Oncorhynchus kisutch (coho salmon) - 1.39 mg/l - 40 d Remarks: (ECHA) |
| Toxicity to daphnia and other aquatic invertebrates(Chronic toxicity) | NOEC - Ceriodaphnia dubia (water flea) - 0.74 mg/l - 7 d (US-EPA) |

12.2 Persistence and degradability

| | |
|------------------|--|
| Biodegradability | aerobic - Exposure time 20 d Result: 86 % - Readily biodegradable. Remarks: (IUCLID) |
|------------------|--|

12.3 Bioaccumulative potential

| | |
|-----------------|--|
| Bioaccumulation | Leuciscus idus (Golden orfe) - 3 d - 0.05 mg/l(Toluene) |
| | Bioconcentration factor (BCF): 90 |

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Product**

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself. See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

SECTION 14: Transport information**14.1 UN number**

ADR/RID: 1294 IMDG: 1294 IATA-DGR: 1294

14.2 UN proper shipping name

ADR/RID: TOLUENE
IMDG: TOLUENE
IATA-DGR: Toluene

14.3 Transport hazard class(es)

ADR/RID: 3 IMDG: 3 IATA-DGR: 3

14.4 Packaging group

ADR/RID: II IMDG: II IATA-DGR: II

14.5 Environmental hazards

ADR/RID: no IMDG Marine pollutant: no IATA-DGR: no

14.6 Special precautions for user

None

14.7 Incompatible materials**Other regulations**

Hazchem Code : 3YE

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

Therapeutic Goods (Poisons Standard) : No poison schedule number allocated
Instrument

SECTION 16: Other information

-

Full text of H-Statements referred to under sections 2 and 3.

H225 Highly flammable liquid and vapor.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.

SIGALD- 34866

Page 11 of 12

The life science business of Merck operates as MilliporeSigma in the US and Canada



H336 May cause drowsiness or dizziness.
H361 Suspected of damaging fertility or the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure if inhaled.

Further information

The information is believed to be correct but is not exhaustive and will be used solely as a guideline, which is based on current knowledge of the chemical substance or mixture and is applicable to appropriate safety precautions for the product. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.